

2/PRTS

10/018681

531 Rec'd PCT/P 19 DEC 2001

PIEZOELECTRIC ACTUATOR

Inv.
A1

[0001] Prior Art

Inv.
A2

Sub.
A3

[0002] The invention relates to a piezoelectric actuator, for instance for actuating a mechanical component such as a valve or the like, in accordance with the generic characteristics of the preamble to the main claim.

Sub.
A4

[0003] It is widely known that by utilizing the so-called piezoelectric effect, a piezoelectric element can be constructed from a material with a suitable crystalline structure. When an external electrical voltage is applied, a mechanical reaction of the piezoelectric element takes place, which depending on the crystalline structure and the regions where the electrical voltage is applied causes a compression or tension in a predeterminable direction.

[0004] The aforementioned piezoelectric actuators are often used in the positioning of valves. Among other factors, it must be considered here that their stroke capacity for actuating a valve tappet, for instance, is relative slight for a comparatively great force. To increase the useful stroke, it is therefore sometimes usual to provide a mechanical or hydraulic travel booster. Such mechanical or hydraulic travel boosting systems, however, entail greater effort and therefore greater expense as well.

10018681-040203

Pub. A5

1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

[0008] With the invention, a long, narrow piezoelectric actuator is created in a simple way that is mechanically relatively invulnerable, for instance to vibration when used

in the engine compartment of a motor vehicle. Because of the long stroke resulting from the long, narrow design, a stroke boost can be dispensed with, and in principle, tensile forces or compressive forces can be generated by the piezoelectric actuator.

[0009] Because a flexible intermediate layer, for instance of plastic such as a polymer or the like, is mounted between the stabilizing elements and the piezoelectric element, a longitudinal motion, which represents a relative motion between the piezoelectric element and the stabilizing element, can be allowed. An oscillating motion of the piezoelectric element in the X or Y direction can be avoided, however. It is thus possible in a simple way to prevent bending tensions in the piezoelectric element that could possibly lead to the destruction of the piezoelectric actuator.

[0010] The aforementioned concrete embodiment furnishes downward-oriented compressive forces and is not temperature-compensated. In a second embodiment, the piezoelectric element and the stabilizing elements are of ceramic materials, which have essentially the same coefficients of temperature expansion, so that this embodiment is temperature-compensated. The stabilizing element is here as well held between a base plate and a fixation edge in the housing, but the base plate rests on the housing via a spring.

1001831-04002

[0011] In this last embodiment, the stabilizing element is mechanically coupled to the piezoelectric element in such a way that the temperature-dictated expansions of the piezoelectric element and of the stabilizing elements cancel one another out in the effective direction in such a way that the actuating element remains in its position, or in other words no zero-point drift occurs. The piezoelectric element is held between the base plate and a spring plate, which via a prestressing spring likewise rests on the housing and guides the actuating element. Here the force of the prestressing spring must be substantially greater than that of the spring on the base plate, so that the different temperature expansions between the housing and the material comprising the piezoelectric element are compensated for via the spring. Additional provisions for temperature compensation, as was often provided until now by hydraulic coupling, are no longer necessary here.

[0012] In the invention, the piezoelectric element can be constructed of transversely stacked piezoelectric layers and thus exerts a compressive force on the actuating element, or of longitudinally stacked piezoelectric layers and thus exerts a tensile force on the actuating element.

[0013] In other advantageous embodiments, the stabilizing element comprises piezoelectric layers, each located perpendicular to the layered structure of the piezoelectric element, which piezoelectric layers are triggered with a

voltage in the same way as the piezoelectric element. With this embodiment, in addition to the temperature compensation, the useful stroke is also lengthened by means of the additional stroke of the stabilizing elements. The contacting of the piezoelectric layers can be located in the intermediate layer or outside it.

[0014] In another advantageous embodiment of the invention, two piezoelectric elements are disposed symmetrically to a tension rod, acting as the actuating element, surrounded by the intermediate layer in the housing of the piezoelectric actuator. The piezoelectric elements here are held between a support plate, connected to the tension rod, and a fixation edge in the housing, and the support plate rests on the housing via a spring.

[0015] These and other characteristics of preferred refinements of the invention will become apparent from the claims and the description and the drawings; the individual characteristics, each alone or a plurality of them in the form of subsidiary combinations, can be realized in the embodiment of the invention and in other fields and can represent both advantageous and intrinsically patentable embodiments for which patent protection is here claimed.

[0016] Drawing

Sub.
A7

[0017] Exemplary embodiments of the piezoelectric actuator of the invention with a narrow design, for instance for positioning a valve, will be explained in conjunction with the drawing. Shown are:

[0018] Fig. 1, a section through a non-temperature-compensated piezoelectric actuator with steel stabilizing elements;

[0019] Fig. 2, a detail taken along a section line A-A of Fig. 1, with a first contacting option for the piezoelectric element;

[0020] Fig. 3, a detail taken along a section line A-A of Fig. 1, with a second contacting option for the piezoelectric element;

[0021] Fig. 4, a section through a temperature-compensated, transversely stacked piezoelectric element of the piezoelectric actuator, with a ceramic stabilizing element;

[0022] Fig. 5, a section through a temperature-compensated, longitudinally stacked piezoelectric element of the piezoelectric actuator, with a ceramic stabilizing element;

[0023] Fig. 6, a detail taken along a section line A-A of Fig. 5, with a first contacting option for the piezoelectric element;

[0024] Fig. 7, a detail taken along a section line A-A of Fig. 5, with a second contacting option for the piezoelectric element; and

[0025] Fig. 8, a section through a non-temperature-compensated piezoelectric actuator with two piezoelectric elements disposed one on either side of a tension rod.

[0026] Description of the Exemplary Embodiments

10043634-040302
Lab.
198

[0027] In Fig. 1, a piezoelectric actuator 1 is shown that has a piezoelectric element 2, which in a manner known per se is constructed of piezoelectric sheets of a quartz material with a suitable crystalline structure, so that by utilizing the so-called piezoelectric effect upon application of an external electrical voltage to electrodes 3 and 4, a mechanical reaction of the piezoelectric actuator 1 is effected, in the form of a force F_{useful} . The exemplary embodiment in Fig. 1 is not temperature-compensated and furnishes a compressive force F_{useful} .

[0028] The relatively long, slender piezoelectric element 2 is pressed by its upper end against a base or support plate 8 by means of a prestressing spring 6 and a spring plate 7, disposed above this spring, on the lower end of the piezoelectric element. The support plate 8 is braced with stabilizing elements 9, disposed symmetrically on both sides of the piezoelectric element 2, which are braced at the top

and bottom on the housing 10 of the piezoelectric actuator 1. Between the stabilizing elements 9 and the piezoelectric element 2 is a flexible plastic, such as a polymer, located longitudinally in the form of an intermediate layer 11. The task of the flexible intermediate layer 11 is to allow a longitudinal motion, that is, the relative motion between the piezoelectric element 2 and the stabilizing elements 9, but to prevent an oscillating motion of the piezoelectric element in the X or Y direction.

[0029] From Figs. 2 and 3, possibilities for a connection of the contacts 3 and 4 of the piezoelectric element 2 are suggested; these can be effected in either the X or Y direction and can thus be located either in the intermediate layer 11 or outside it.

1004664-040201
Sub.
199

[0030] A second exemplary embodiment of a piezoelectric actuator 20 is shown in Fig. 4; here, components functioning the same are identified by the same reference numerals as in Fig. 1. In the arrangement of Fig. 4, there is one piezoelectric element 21, and there are stabilizing elements 22 that are made from a ceramic material with approximately the same coefficient of temperature expansion as the piezoelectric element 21. The support plate 8 is prestressed here in the housing 10 via a spring 23; the prestressing force of the spring 23 must be substantially greater than that of the prestressing spring 6, so that the different temperature expansions between the housing 10 and the piezoelectric

10018631-040202
Feb. 1964
cont.

element 21 can be compensated for via the spring 23. However, it is also possible to omit the spring 23. Then the piezoelectric element 21 would be held together by the upper support plate 8, analogously to what Fig. 1 shows, and optionally also by a lower support plate. The upper support plate 8 would, as in Fig. 1, rest on a shoulder of the housing 10. The spring 23 prevents the stabilizing element 22 from being subject to tensile stress that can be caused by the prestressing of the piezoelectric element. This prestressing is accomplished with the aid of the spring 6.

[0031] An actuation of the piezoelectric actuator 20, in this exemplary embodiment as well, leads to an axial expansion of the piezoelectric element 21 and thus to a compressive force F_{useful} , counter to the prestressing of the prestressing spring 6. Since here as well the piezoelectric element 21 and the stabilizing elements 22 have essentially the same coefficients of temperature expansion, the temperature-caused expansions of the piezoelectric element 21 and of the stabilizing element 22, in the proposed mechanical mounting, cause the influences of the two elements 21 and 22 to be cancelled out in the effective direction. Thus the actuating element, connected to the spring plate 7 of the piezoelectric element 21, can remain in its position.

[0032] A third exemplary embodiment of a piezoelectric actuator 30 is shown in Fig. 5; once again, components that function the same are provided with the same reference

Pub.
H9
eoid.

numerals as in Fig. 1 or Fig. 4. In the arrangement of Fig. 5, in contrast to the disposition of Fig. 4, only one piezoelectric element 31 is provided with longitudinally stacked piezoelectric layers. An actuation of the piezoelectric actuator 30 in this exemplary embodiment leads to an axial shortening of the piezoelectric element 31 and thus to tensile force F_{useful} that acts on the actuating element.

10013631-040621-010

[0033] In Figs. 6 and 7, once again possibilities for a connection of the contacts 3 and 4 of the piezoelectric element 31 are suggested; these can again be effected with suitably oriented piezoelectric layers in either the X or Y direction and can thus be located either in the intermediate layer 11 or outside it.

Pub.
H10

[0034] From Fig. 8, a further exemplary embodiment of a piezoelectric actuator 40 can be seen; once again, the components functioning the same are provided with the same reference numerals as in Fig. 1, Fig. 4 or Fig. 5. In the arrangement of Fig. 8, two piezoelectric elements 41 and 42 are disposed symmetrically to a tension rod 43, which represents the actuating element. The piezoelectric elements 41 and 42 and the tension rod 43 are disposed, surrounded by the intermediate layer 11, in the housing 10 of the piezoelectric actuator 40. The piezoelectric elements 41 and 42 here are furthermore held between a support plate 44, connected to the tension rod, and via the spring 23 on an upper fixation edge in the housing 10 and a lower fixation

edge in the housing 10. This arrangement furnishes a tensile
force as the force F_{useful} and is not temperature- compensated.

Ans. 1
A''

10013694-040233